

# Centre-axle timber/stanchion trailer - without platform



## Product benefits

- Lightweight frame made from special high-strength NAXTRA steel
- ExTe trailer stanchions incl. 2-part ExTe stanchions 144-S with bolt fastening (load capacity: 7 t/pair)
- Stanchions mounted via welded clamps
- Gripper deflector plates on frame side members
- Air suspension unit in off-road design
- Installation of axles from well-known manufacturers such as SAF or BPW
- OPTIONAL: Steel stud plate cover between frame side members
- OPTIONAL: Fixed crane bracket at front, incl. bogie fixation
- OPTIONAL: Steel pipe transverse support, tapered on both outer sides, mounted via clamp fastening
- OPTIONAL: 20 t total weight with 2 x 10 t air-sprung axles and twin tyres
- OPTIONAL: Mudguard easily removable with spring compressor, for simple snow chain application
- OPTIONAL: Autonordic heavy-duty band winch with belt

## Product details

### TYPE DESIGNATION

CENTRE-AXLE STANCHION TRAILER - WITHOUT PLATFORM

---

### WEIGHTS

Gross weight (perm.): 18 t

Gross weight (techn.): 19 t with 1 t drawbar load

Tare weight: approx. 3.1 t

---

### DIMENSIONS

Frame length: approx. 5,000 mm

Total width: 2,550 mm

Unladen loading height up to upper stanchion edge: approx. 1,320 mm  
(trailer stanchions not in wheel area)

---

### FRAME

Naxtra centre-axle welded steel frame construction

Drawbar with height-adjustable (- approx. 110 mm) screw-on drawbar eye, 50 mm,  
for centre-axle heavy-duty coupling, for 0 mm truck superstructure (not low-coupled)  
and unladen coupling height approx. 800 - max. 1,000 mm  
gripper deflector plates approx. 200 mm long

---

### CHASSIS

Air suspension without lifting and lowering device,  
bellow diameter 360 mm

---

### BRAKE SYSTEM

Brake system according to EC Directive 71/320 or ECE R13

Two-line brake

EBS - electronic brake system

Knorr 2S2M = 2nd axle sensed

RSS - stability program

Spring-loaded parking brake on 2nd axle

Steel air tank

Brake valves etc. mounted with protection or cover

---

### FLOOR

Cover between the frame longitudinal beams, 12 mm resin-coated panels

---

## **STANCHION BODY**

2 ExTe trailer stanchions 144-S with 2-part stanchions incl. bolt fastening,  
load height: max. 2,800 mm, load capacity of stanchions: max. 7 t per pair (minimal  
stanchion inclination inwards), mounted/movable by means of welded clamp fastening  
1 lashing point for belt hooks per stanchion on left and right

---

## **ELECTRICAL EQUIPMENT**

24 V lighting system according to EC Directive 76/756/EEC  
2 seven-chamber tail lights in underride protection  
LED side marker lights  
2 clearance lamps  
2 contour lights on underride protection  
Fixed cable(s) with 2 x 7-pin or 1 x 15-pin connector

---

## **PAINTWORK**

Blasted with steel granulate, treated with zinc dust primer and spray painted  
2-component acrylic paints for commercial vehicles (standard RAL or truck colour)

Stanchions in original orange signal colour  
Plastic and hot-dip galvanised parts unpainted,  
powder-coated attachments/installation parts black

Reflective contour marking strips across entire length of sides and on the rear (white on sides and  
red at rear by default), according to ECE 48

---

## **ACCESSORIES**

Rear markings as per ECE standards

---

## **ATTACHMENTS**

Wheel chock(s) as per regulations  
4 single wheel plastic mudguards with spray protection as per regulations (non-removable)  
Aluminium underride protection, coated white  
"Schwarz Müller" rubber apron on the underride protection, over the entire width  
Side impact protection made from aluminium profiles as per regulations, coated black

---

## **AXLES**

Low-maintenance air-sprung axles, each with 9 t axle load  
S-cam brake 420/180 mm, autom. brake linkage adjuster  
Reinforced axle beam (off-road version)

Tyres :

4 x 385/65 R 22.5 160J, manufacturer as per factory specifications

4 steel wheel rims 11.75 x 22.5, 10-hole, without rim offset, silver

---

### **SUPPORT FIXTURES**

1 mechan. support jack with hand crank at front

---

## Product impressions



Total of 2 ExTe stanchions incl. dual-part ExTe stanchions 144 with screw attachment (loading capacity 7 t/pair)



Height-adjustable drawbar for centre-axle heavy-duty coupling



