

2-axle 3-way tipper semitrailer - building site - reinforced



Product benefits

- Reinforced 10 t axles for technical load capacity up to approx. 35 t
- Stable and torsionally rigid chassis construction with additional torsion tubes for 3-way tipping
- Conical, trapezoidal profile side members in high-strength, lightweight design with small bottom panels for high dent resistance and shock absorption
- Full-steel welded construction with fine-grained special steel floor panels, 5 mm
- Foldable underride protection for road-finishing use
- Foldable lashing rings
- Installation of axles from well-known manufacturers such as SAF or BPW
- OPTIONAL: Spare wheel bracket with swivel boom and winch on front wall
- OPTIONAL: Electropneumatic side wall pendulum locking
- OPTIONAL: Standing platform at front wall comprising aluminium safety grid and guardrail
- OPTIONAL: Plastic roller tarpaulin incl. aluminium tube and hand crank
- OPTIONAL: Dosing unit for hinged rear wall with towing pin

Product details

TYPE DESIGNATION

2-AXLE 3-WAY TIPPER SEMITRAILER - BUILDING SITE - REINFORCED

For handling bulk materials such as sand, gravel, rubble, ground excavation etc. on building sites

DIMENSIONS

Internal length: approx. 7,150 mm

Internal width: approx. 2,420 mm

Total width: 2,550 mm

Loading height, unladen: approx. 330 mm over fifth-wheel coupling

FRAME

Naxtra welded steel frame construction

Connector lock for tipper body with cross-over protection

Replaceable 2" kingpin

CHASSIS

Air suspension with autom. lowering device via inductive switch and lowering lock via rotary switch on semitrailer

Air suspension unit with low-maintenance 430 mm disc brake axles, off-road version,
2 x 10 t rigid, wheelbase 1,310 mm

Autom. lifting front axle = raised or lowered according to weight, as well as forced lowering incl. integr. speed-restricted moving-off aid with button operation in cab (no button installation on our part)

Tyres :

4 x 445/65 R 22.5 168K, manufacturer as per factory specifications

4 steel wheel rims 14.00 x 22.5, 10-hole, without rim offset, silver

SUPPORT FIXTURES

2 steel support legs, height-adjustable (only detachable when unladen)

BRAKE SYSTEM

Brake system according to EC Directive 71/320 or E CE R13

Two-line brake

Spring-loaded parking brake on both axles

EBS - electronic brake system

Wabco 2S2M = one axle sensed

RSS - stability program

Steel air tank

TIPPING SYSTEM

1 tipper cylinder for 3-way tipping, approx. 70 t initial lifting force,

1 arrester cable

1 pipe system with screw coupling DN20

TIPPER BODY

ROLLER TARPAULIN

ELECTRICAL EQUIPMENT

24 V lighting system according to EC Directive 76/756/E WG

2 seven-chamber tail lights

LED side marker lights

2 clearance lamps

2 contour lights

2 x 7-pin / 1 x 15-pin socket

PAINTWORK

Blasted with steel granulate, treated with zinc dust primer and spray painted 2-component acrylic paints for commercial vehicles (standard RAL or truck colour)

Plastic and hot-dip galvanised parts unpainted,
powder-coated attachments/installation parts black

Reflective contour marking strips across entire length of sides and all-round contour marking at rear (white on sides and red at rear by default), according to ECE 48

CONTOUR MARKINGS

ACCESSOIRES

ATTACHMENTS

Wheel chock(s) as per regulations

Noise dampers

Single wheel plastic mudguards with spray protection as per regulations

Aluminium trapezoidal underride protection, foldable, unpainted

WEIGHTS

Gross train weight (perm.): 40 t

Gross weight (techn.): 36 t

Axle assembly load (techn.): 20 t

Fifth-wheel load (techn.): 18 t

Payload: approx. 25 t (but techn. configured for loads up to approx. 35 t)

Tare weight: approx. 6.4 t

TIPPING LOADING RAMP

Full-steel welded construction with fine-grained special steel floor panels, 5 mm (slight floor unevenness possible due to weld distortion)

SIDE WALLS

Fixed steel plate front wall, 3 mm, approx. 1,360 mm high with excavator protection, lashing eyes, ladder and retaining brackets

2-part aluminium hollow profile side walls, 60/40 mm, approx. 1,200 mm high, hinged with manual central locking (operated separately for each wall), foldable when empty = upper self-aligning bearings with screw retention

Steel plate rear wall, 4 mm, approx. 1,300 mm high,
hinged with raised bearing and autom. pneumatic locking
1 handle

POSTS/COVER

ACCESSORIES

Rear markings as per ECE standards

STEERING

POSTS

2 fixed centre posts in side wall height
2 fixed rear corner posts, raised, with welded discharge chute
(ground clearance when tipped: approx. 550 mm)

SIDE WALLS/POSTS

LANDING GEAR

AXLES

WHEELS

BRAKES

HYDRAULICS

TARPAULIN

LIGHTING/ELECTRICAL EQUIPMENT

LABELLING

DRAWGEAR

HARDOX TIPPER BODY

ROLL COVER

THERMAL INSULATION: R-VALUE 1.65 MÂ²K/W (AT 20Â°C)

TOWING DEVICE

TIPPING TROUGH

Product impressions



Conical trapezoidal profile side members in high-strength, lightweight design with small bottom panels for high dent resistance and shock absorption



Steel sheet rear wall, hinged with raised bearing and autom. pneumatic lock



Fixed steel sheet front wall with lashing eyes, ladder and retaining brackets



2-axle 3-way tipper semitrailer - building site - reinforced



Stable and torsionally rigid chassis design with additional torsion tubes for 3-way tipping



Foldable underride protection for road-finishing use



Manual central locking to open the side walls using a lever and central locking shaft



OPTIONAL: Spare wheel bracket with swivel boom and winch on front wall

