

# 3-way tipper body for 4A truck - building site



## Produktvorteile und Optionals

- Insulated hollow chamber body for slow cooling, freezing and adhesion of load
- Tipper body construction using conical, trapezoidal profile side members in high-strength, lightweight design with small bottom panels for high dent resistance and shock absorption
- Torsionally rigid, weight-optimised subframe construction
- Hard chrome-plated, high-quality tilt cylinder
- OPTIONAL: Bordmatic (= hydraulically folding side wall) on left side
- OPTIONAL: Reinforced side walls with material-repellent membrane construction made from fine-grained special steel panels
- OPTIONAL: Electropneumatic side wall locking with switch operation in cab
- OPTIONAL: Aluminium flap on lateral central locking shaft
- OPTIONAL: Foldable lashing rings
- OPTIONAL: Foldable aluminium underride protection for road-finishing use
- OPTIONAL: Front and rear crane mounting with reinforced subframe

## Fahrzeugdetails

### TYPE DESIGNATION

3-WAY TIPPER BODY ON 4-AXLE TRUCK - BUILDING SITE For handling bulk materials such as sand, gravel, rubble, ground excavation etc. on building sites

---

### WEIGHTS

Body weight: approx. 3.3 t

---

### DIMENSIONS

Internal length: approx. 5,700 mm Internal width: approx. 2,420 mm Load volume: approx. 15 m<sup>3</sup> Total width: 2,550 mm Body height, loading height etc. can only be checked and announced upon specification of the exact truck data

---

### PAINTWORK

Blasted with steel granulate, treated with zinc dust primer and spray painted 2-component acrylic paints for commercial vehicles (standard RAL or truck colour) Plastic and hot-dip galvanised parts unpainted, powder-coated attachments black Reflective contour marking strips across entire length of sides (continuing onto truck cab) and all-round contour marking at rear (white on sides and red at rear by default), according to ECE 48

---

## **ACCESSORIES**

Rear markings as per ECE standards

---

## **ATTACHMENTS**

Tipper body rubber centre support Bracket for wheel chock(s) Mud flaps for rear mudguards Shovel and brush brackets Rubber skirting on side walls on both sides

---

## **SIDE WALLS**

Fixed steel plate front wall, 4 mm, approx. 1,250 mm high 1-part reinforced aluminium hollow profile side walls, 60/4/3 mm, approx. 1,080 mm high, foldable with extended swivel bolt locks and spring lifting aid, hinged with pneumatic locking operated from cab 4 mm steel sheet rear wall, approx. 1,180 mm high, hinged with raised bearing and pneum. locking opened from cab Fixed rear corner posts, raised, side-mounted, with discharge chute

---

## **SUBFRAME**

Continuous side members with tilt cylinder bearings and outriggers Body height above chassis: approx. 500 mm Connector lock for tipper body with cross-over protection

---

## **HIGH-PRESSURE HYDRAULIC TIPPING SYSTEM**

27 t tilt cylinder for 3-way tipping, with safety rope, 80 l pump for direct flange mounting, 60 l oil reservoir with oil filling, pneum. tip valve with overpressure protection and actuation in cab

---

## **TIPPING LOADING RAMP**

Full-steel welded construction with fine-grained special steel floor panels, 6 mm HARDOX HB450 (slight floor unevenness possible due to weld distortion)

## Impressionen



OPTIONAL: Bordmatic (= hydraulically folding side wall) on left side



OPTIONAL: Reinforced side walls with material-repellent membrane construction made from fine-grained special steel panels



4 mm steel sheet rear wall, approx. 980 mm high, hinged with raised bearing and pneum. lock that can be operated from the cab and unit can be partially folded down



Tipper body design with conical trapezoidal profile side members in high-strength, lightweight design with small bottom panels for high dent resistance and shock absorption



OPTIONAL: Foldable aluminium underride protection for road-finishing use



OPTIONAL: Foldable lashing rings



3-way tipper body on 4-axle truck - building site



Hard chrome-plated, high-quality tilt cylinder

